3M Particulate Respirators 8210 and 8110S, N95

Issue Date 01/01/04

The 3M[™] Particulate Respirator 8210, N95 is designed to help provide quality, reliable worker protection against certain non-oil based particles. The 3M[™] Particulate Respirator 8110S, N95 offers the same protection for those workers with smaller faces. The 8210 and the 8110S offer a number of benefits to you and your workers.

NIOSH approved N95

• At least 95% filtration efficiency against solid and liquid aerosols that do not contain oil.* TC-84A-0007

Advanced Electret Media

• Advanced electrostatically charged microfibers make breathing easier and cooler.

Helps provide worker protection

• Because they are comfortable to wear and easy to use, workers are quick to accept and use maintenancefree respirators, like the 8210 and 8110S. Studies have shown they can provide protection equivalent to a rubber facepiece respirator...at much lower cost and greater convenience.

Lightweight construction

- Promotes greater worker comfort.
- Contributes to increased wear time.

Adjustable noseclip

- Helps provide a custom fit and secure seal.
- Reduces the potential for eyewear fogging.



3M[™] Particulate Respirator 8210, N95 (Inset photo: 3M[™] Particulate Respirator 8110S, N95)

Suggested Applications



GrindingSanding

- Sweeping
- Bagging
- Other dusty
- operations

 Woodworking
- Foundries



or call 3M OH&ESD Technical Service in U.S.A. 1-800-243-4630. In Canada, call 1-800-267-4414

Respirators Per Box		Те
8210 & 8110S	Respirators Per Case	
20	160	

Use For:

- Solids such as those from processing minerals, coal, iron ore, flour, and certain other substances.
- Liquid or non-oil based particles from sprays that do not also emit harmful vapors.

Do Not Use For:

Gases and vapors, including those present in paint spray operations, asbestos, arsenic, cadmium, lead, 4,4'-methylenedianiline (MDA) or sandblasting. Aerosol concentrations that exceed 10 times the OSHA PEL, or applicable exposure limits, whichever is lower. This respirator does not supply oxygen.

Important

Before using these respirators, you must determine the following:

- 1. The type of contaminant(s) for which the respirator is being selected.
- 2. The concentration level of contaminant(s).
- 3. Whether the respirator can be properly fitted on the wearer's face. Do not use with beards, on other facial hair, or other conditions that prevent a good seal between the face and the faceseal of the respirator.
- 4. Before use of these respirators, a written respiratory protection program must be implemented, meeting all the requirements of OSHA 29 CFR 1910.134, including training, medical evaluation and fit testing.

Time Use Limitation

If respirator becomes damaged, soiled, or breathing becomes difficult, leave the contaminated area immediately and dispose of the respirator.

echnologies



Additional Information

This respirator contains no components made from natural rubber latex.

For more information, please contact:

3M Occupational Health and Environmental Safety Division (OH&ESD)

In the U.S., contact: Sales Assistance 1-800-896-4223 Technical Assistance 1-800-243-4630 Fax On Demand 1-800-646-1655 Internet http://www.3M.com/occsafety For other 3M products 1-800-3M HELPS

In Canada, contact:

3M Canada Company, OH&ESD P.O. Box 5757 London, Ontario N6A 4T1 Sales Assistance 1-800-265-1840, ext. 6137 Technical Assistance (Canada only) 1-800-267-4414 Fax On Demand 1-800-646-1655 Internet http://www.3M.com/CA/occsafety

Technical Assistance In Mexico 01-800-712-0646 5270-2255, 5270-2119 (Mexico City only) Technical Assistance In Brazil 0800-132333 Fax On Demand O.U.S. Locations 1-651-732-6530

3M Occupational Health and Environmental Safety Division 3M Center, Building 235-2W-70 St. Paul, MN 55144-1000